

KÖSTER Flex Fabric

Prospekt / Šifra proizvoda
Izdato: 19. Novembar 2009

11.05

Plasti na mrežica za ojačanje tankih slojeva hidroizolacije

Opis

KÖSTER Flex Fabric je visoko elastična, dobro pletena plastična mrežica sa velikom otpornošću na kidanje.

Korišteni citirani tehnički listovi

KÖSTER KBE Liquid Film	Art.-No. 1.13
KÖSTER Dachflex®	Art.-No. 7.06
KÖSTER BD 50	Art.-No. 7.09

Tehnički podaci

Baza	100 % polipropilen
Boja	bela
Površina	perforirana
Težina	Oko. 66 g / m ²
Otpornost na kidanje	Po dužini 252 N / 5 cm unakrsno 181 N / 5 cm
Otpornost na pucanje	Po dužini oko. 38 % Unakrsno oko. 105 %
Temperaturna otpornost	- 30 °C do + 150 °C

Priloge aplikacije

KÖSTER Flex Fabric je namenjena ojačanje tankih slojeva hidroizolacije kao što su KÖSTER KBE Liquid Film, KÖSTER BD 50 i KÖSTER Dachflex®. KÖSTER Flex Fabric se ručno aplikuje na površinama koje su podložne pukotinama, kao i za spojeve zida-poda, prodora oko cevi i td...

Aplikacija

KÖSTER Flex Fabric se utapa u prvi svež sloj premaza koristeći špaku, valjak ili sl. Zatim se pokriva sledećim slojem premaza koji se nanosi špaklom ili valjkom. Za debljinu sloja pogledati tehnički list. Kajeve mrežice preklopiti jednu preko druge najmanje 5cm.

Pakovanje

50 m² rolna; širina: 100 cm, dužina: 50 m

Skladištenje

Materijal uvati na suvom i hladnom mestu, tako uskladišten materijal može se koristiti neograničeno.

The accurate and thereby effective and successful application of our products is not subject to our control. The guarantee can therefore only be applied to the quality of our products within the scope of our terms and conditions, not, however, for their effective and successful application. These guidelines replace all previous ones.