

# KÖSTER

Tehni ki podaci / Artikal broj

3.062

Važi od 07. Januara 2010.

## MAUTROL® FLEX 2C

### 2-KOMPONENTNA VODORASTVORLJIVA INJEKCIONA TE NOST ZA INJEKTIRANJE POD NISKIM PRITISKOM, PROTIV RASTU E VLAŽNOSTI

#### OPIS

Mautrol® Flex 2c je dvokomponentna niskog viskoziteta injekciona te nost na akrilnoj osnovi.. Sposobnost komponente B da se transformiše u želatinoznu strukturu, omogu ava MAUTROL®FLEX 2C-u da se injektira i u veoma vlažan zid bez prethodnog dreniranja MAUTROL®FLEX 2C ne napada armaturu.

#### TEHNI KI PODACI

Karakteristika	zaptiva	pora/ odbija vode	
komp. B		komp. A	
- Osnova		Akril	
Estar			
- Obojenost		Delimi no	
Providan		providedan	
- Specifi na gustina		1.03 g/ cm <sup>3</sup>	1.09 g/ cm <sup>3</sup>
- Specifi na gustina mešavine		1.07 g/ cm <sup>3</sup>	
- Vreme primene		od 1.0h – 18.0h	
		( u zavisnosti od sadržaja vode)	
- Odnos mešanja	100 delova/ težina		100 delova/ težina

#### POLJA APLIKACIJE

Mautrol® Flex 2C je specijalno dizajniran za injektiranje metodom, niskog pritiska, da formira horizontalne barijere u zidanim, betonskim i gipsanim zidovima protiv rastu e vlage. On tako e pove ava vrstinu konstrukcija od cigle i prirodnog kamena. Ne aplikovati kod aktivnih prodora vode pod pritiskom.

#### APLIKACIJA

Za formiranje horizontalne barijere neophodno je izbušiti rupe iznad zemlje ili iznad nivoa podloge. Rupe treba da budu postavljene u dve paralelne linije, asimetri no, na 10 – 15 cm. udaljene jedna od druge. Ubušiti ih horizontalno na 5 cm od kraja zida. Dijametar izbušenih rupa zavisi od dijametra odabranih pakera. Posle uklanjanja prašine od bušenja iz rupa, utisnuti patron portove. Pomešati komponentu A sa vodom (po tabeli) i onda dodati komponentu B i ponovo dobro izmešati. **NIKADA NE MEŠATI KOMPONENTE A I B BEZ PRETHODNOG DODAVANJA VODE!!!** Injektovati smešu sa pogodnom opremom

za injektovanje (npr. klipna pumpa) preko portova dok se zid potpuno ne zasiti. Mogu e je injektovanje vršiti pojedina no ili grupno kroz nekoliko portova odjednom. Portovi mogu biti više puta injektovani pre nego materijal po ne da se pretvara u gel. Po završenom injektiranju ukloniti patron portove i rupe popuniti sa Mautrol Borehole suspenzijom.

#### TABELA ODNOSA MEŠANJA SA VODOM

% vlažnosti pretvaranja zida	komp. A (težina)	Voda (težina)	komp. B (težina)	Vreme u gel ( 20° C)
0 – 5 M. - %	1	10	1	18 h
5 – 10 M. - %	1	7	1	10 h
10 – 15 M. - %	1	5	1	6 h
> 15 M. - %	1	4	1	4 h

#### POTROŠNJA

- Oko 0,2 ltr. / Lin. M. po cm debljine zida.

#### PAKOVANJE

- Komponenta A 10 kg. konzerva
- Komponenta B 10 kg. konzerva

#### SKLADIŠTENJE

Na hladnom, zašti eno od mraza. U originalnom pakovanju rok upotrebe 2 godine.

#### Pri radu koristiti zaštitnu opremu!

The accurate and thereby effective and successful application of our products is not subject to our control. The guarantee can therefore only be applied to the quality of our products within the scope of our terms and conditions, not, however, for their effective and successful application. These guidelines replace all previous ones.